@lgood hardware



7282.F60L Allgood Hardware 72 Series Euro Profile Cylinder Mortice Apartment Lock

- Independently tested to BS EN 179:2008

3	7	6	B	1	3	4	2	A	B
3	7	6	B	1	3	4	2	A	D

- Case Depth A = 92mm
- Case Height = 165mm
- Backset B = 60mm
- Left hand Controlled outside Lever
- Right hand inside lever free to escape
- UK Right hand Lock ISO 5.0
- Radius Outer Forend
- Heavily sprung 8mm split follower for lever handles
- CE Marked & Certifire approved CF347
- Incorporated in successful fire tests and assessed to BS EN 1634-1 and BS 476 Pt 22 up to 90 minutes on timber doors and up to 240 minutes on metal doors
- Reversible latchbolt without opening lockcase
-

Available Finishes: SS · PS · BF

- Bolt through fixing holes for furniture
- Supplied with reversible strike plate and mortar guard
- Supplied with XX9069 spilt spindle
- Lever handles on both sides will withdraw latchbolt. If deadbolt is projected, the inside handle only will withdraw both bolts. Door then remains unlocked until manually re-locked from outside or turn from inside.
- Replacement Forend Screws
  - *M5 x 6 Pozi csk M/C screws* order code ##FEScrew *3 per lock*
- Replacement Strike Plate Screws
  - 8G x 1.5 inch pozi csk wood screw order code ##SP1.5Screw *1 per lock*
  - 8G x 1 inch pozi csk wood screw order code ##SP1Screw *4 per lock*
- Construction Code for Product Information 'CCPI' Assessed product set 015200202/0228
- 10 year mechanical warranty



