RedLock

@llgood



9990NHD Allgood Hardware 99 Series Redlock® Euro Profile Cylinder Mortice Escape Nightlatch

- Independently tested to BS EN 179:2008

3	7	6	B	1	3	4	2	A	B
3	7	6	B	1	3	4	2	A	D

- Compatible with every Allgood lever handle
- Incorporated in a successful fire test and assessed to BS EN 1634-1 and BS 476 Pt 22 up to 90 minutes on timber doors and 240 minutes on metal doors
- CE Marked and Certifire approved CF 623
- Heavily sprung 8mm follower for lever handles
- Reversible latchbolt without opening lockcase
- Bolt through fixing with 38mm centres for furniture
- Supplied with reversible strike plate and mortar guard
- 3 part low friction latchbolt 19.8mm projection
- Anti Thrust Bolt
- UL Listed and complies with ANSI A156.115.1. Suits standard ANSI preparation for metal doors
- Internal lever 'always free to escape'
- 35mm-55mm doors requires separate split spindle. Please specify 1 no. XX9069
- 56mm-76mm doors requires separate split spindle. Please specify 1 no. XX9070
- Construction Code for Product Information 'CCPI' Assessed product set 015200202/0228
- 10 year mechanical warranty

Available Finishes: SS · PS · BF



