




9946N5R Allgood Secure 99 Series Vertical Euro Profile Solenoid Redlock® 12v DC Fail Safe (Right hand lever controlled)

- Compatible with every Allgood lever handle
- Outside handle controlled, lever withdraws latch bolt when solenoid is activated
- Inside lever always free to escape
- Reversible 19.8mm 3-part low friction deadlocking latch-bolt
- Supplied with reversible strike plate and mortar guard
- 12v DC fail safe *[fail unlocked/open]*
- 200mA solenoid current draw
- Monitoring – Latch bolt, Request to exit and door status
- Supplied with simple push fit connections, plus a 5-metre doorway cable loom
- Additional 15 mm of lock mortise depth required to accommodate lock and cable loom
- Incorporated in a successful fire test and assessed to BS EN 1634-1 and BS 476 Pt 22 up to 90 minutes on timber doors and 240 minutes on metal doors
- CE Marked & Certifire approved CF 623
- Independently tested to BS EN 179:2008

3 7 6 B 1 3 4 2 A B

3 7 6 B 1 3 4 2 A D

- Underwriters Laboratories UL 10C electronic locking
- Compliant with ANSI A156.115.1. Suits standard ANSI preparation for metal doors
- Construction Code for Product Information 'CCPI' Assessed product set [015200202/0228](https://www.allgood.co.uk/015200202/0228)
- 10-year mechanical warranty, 1-year electrical warranty (solenoid and microswitches)



Available Finishes: SS · PS · BF

