



**CONSTRUCTION PRODUCTS REGULATION 2011
DECLARATION OF PERFORMANCE
No. DOP-AGD-343**

1. Unique identification code of the product-type:

**9943F5 – 9943F6 – 9943KT5 – 9943KT6 – 9943KTF5 – 9943KTF6 – 9943N5 - 9943N6
9944F5 – 9944F6 – 9944KT5 – 9944KT6 – 9944KTF5 – 9944KTF6 – 9944N5 – 9944N6**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

9943 – 9944

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For use on fire and smoke compartmentation doors
Or
Escape route doors (For other products such as exit devices)**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Allgood Ltd
63-83 Brearley Street, Birmingham B19 3NT**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 14846:2008

Notified testing laboratory No.2812 performed the type testing and issued test reports

8. European Technical Assessment

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom under the sole responsibility of the manufacturer identified above

9. **Declared performance**

Essential characteristics	Performance	Harmonised technical specification
Self closing ability	Grade 8 = 200kg door mass with 15N maximum closing force	EN 14846:2008
5.4 Door mass and closing force Annex A Fire/Smoke test requirements	Return force of latch bolt > 2.5N	
Durability of self-closing 5.3.2 Durability of latch action	Grade A = 50,000 test cycles with no load on latch bolt	
Resistance to fire E (integrity) I (insulation) (for fire doors) 5.5 Suitability for use on fire/smoke doors	Grade C = with a minimum classification time of 30min	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Signed for and on behalf of the manufacturer by:



Stewart Lauder – Managing Director

Date of Issue: 14-11-2025

Allgood Ltd
63-83 Brearley Street,
Birmingham
B19 3NT