



9134NE Allgood Hardware Fully Concealed Electro-Magnetic Hold Open Door Closer for Single Action Doors

- Independently tested to BS EN 1155:1996

3	8	6/3	1	1	3
---	---	-----	---	---	---

- For Single Action doors
- Fully concealed door mounting
- CAM action mechanism for easy operation
- Adjustable closing power (3-6)
- Maximum door weight: 120kgs
- Maximum door width: 1400mm
- Minimum Door thickness 54mm
- Minimum Door width to meet ADM/BS8300 at EN3: 950mm
- Integrated hold open device with adjustable holding force 25Nm to 78Nm
- Adjustable hold open from 80° - 120°
- Requires 24vDC $\pm$ 15% (0.058a / 1.4W) power supply from transformer and relay interface with Fire Alarm System
- CE Marked & Certifire CF6022
- Incorporated in successful fire tests and assessed to BS EN 1634-1 and BS 476 Pt 22 up to 60 minutes on timber doors
- Intumescent Pack (not supplied) order code XX9134FPNE
- Adjustable latch action
- Adjustable closing speed
- CCPI Approved [015200215/0328](https://www.ccpi.co.uk/015200215/0328)
- 10 year manufacturing / 2 year electrical warranty

Available Finishes: SN · PC · BF

