



98181N Surface Mounted Electromagnetic Hold Open & Free-Swing Overhead Door Closer

- Independently tested to BS EN 1155:1996 / BS EN 1154:1996

3	8	3-4	1	1	3
---	---	-----	---	---	---

Fig 1 – Fig 61

- Maximum door weight: 80kg
- Maximum door width: 1110mm
- Universal Application Figure 1 & 6
- Mechanism Rack & Pinion
- Non handed
- Incorporated in successful fire tests and assessed to BS EN 1634-1 and BS 476 Pt 22 up to 120 mins on timber doors
- Certifire approved CF 5517
- CE Marked

3	8	3	1	1	3
---	---	---	---	---	---

Fig 6

- Opening angle Fig 1 / 61 EN3 – 180°
- Fig 1 / 61 EN4 – 110°
- Fig 66 EN3 – 170°
- Adjustable Power size 3-4
- Adjustable closing speed
- Adjustable latching action
- Power supply required = 24v DC
- Current draw = 95mA
- Supplied c/w black power transfer loop, frame mounted connection box and on/off switch
- CCPI Approved [015200215/0328](https://www.allgood.co.uk/015200215/0328)
- 2 year manufacturing warranty

Available Finishes: SS · SA

Please visit our [Spectra Finishes](#) page for more info on these finishes

